SAMSUNG

SAMSUNG Hard Disk Drive Product Guide 2010

We provide the most reliable storage solution

Samsung Electronics

www.samsunghdd.com

Spinpoint is a trademark of Samsung Electronics Co., Ltd.
All brand and product names are trademarks of their respective companies.
Design and specification are subject to change without notice. ⓒ 2010 Samsung Electronics Co., Ltd

January.2010 (Rev.4.0)



Samsung is committed to pursuing the requirements and satisfaction for our customers. Samsung implements proprietary technology, ideal for today's diverse applications. With Samsung HDD, it's not hard to imagine enjoying new, comfortable lifestyle.

Contents

Desktop HDD 04

Mobile HDD 13

Line-up 18

Desktop HDD

Spinpoint F3
Spinpoint F1DT
EcoGreen F3 (F3EG)
EcoGreen F2 (F2EG)
EcoGreen F1DT (F1EG)

Best combination of high capacity, data reliability and solid performance meets all your computing needs.

Spinpoint F3

1 TB / 750 GB / 500 GB / 320 GB / 250 GB / 160 GB

Key Features

- Max.500 GB Formatted Capacity Per Disk
- Serial ATA 3.0 Gbps Interface Support
- Improved recording stability over temperature with PMR
- Advanced dynamic FOD control for best data integrity
- Intelligent compensation of external disturbance
- SATA Native Command Queuing Feature
- Device Initiated SATA Power Management
- Rotational vibration sensor(Optional)
- Environment friendly product with RoHS compliance
- Improved performance with dual-ARM based firmware
- ATA S.M.A.R.T. Compliant
- ATA Automatic Acoustic Management Feature
- ATA 48-bit Address Feature
- ATA Device Configuration Overlay Feature
- NoiseGuard™
- SilentSeek™
- EcoSeek™

Application

Desktop PC / Digital TV / Home Media Servers

Specifications

Capacity[1]	160 GB	250 GB	320 GB	500 GB	750 GB	1 TB
8 MB	HD164GJ	HD254GJ	HD324HJ			
16 MB	HD163GJ	HD253GJ	HD323HJ	HD502HJ		
32 MB					HD754JJ	HD103SJ

DRIVE CONFIGURATIONS

Interface	Serial ATA 3.0Gbps
Rotational Speed	7,200 RPM
Buffer DRAM Size[2]	8 / 16 / 32 MB
Sector Size	512 bytes

PERFORMANCE SPECIFICATIONS

Average Seek time (typical)		8.9 ms
Average Latency		4.17 ms
Data Transfer Rate		
Media to/from Buffer (Max.)		250 MB/sec
Buffer to/from Host (Max.)		300 MB/sec
Drive Ready Time (typical)	320 / 500 GB	8 sec
	750 GB / 1 TB	11 sec

RELIABILITY SPECIFICATIONS

Non-recoverable Read Error	1 sector in 10^{15} bits
Start/Stop Cycles	50,000

ACOUSTICS[2]

Idle	320 / 500 GB	2.5 Bel
	750 GB / 1 TB	2.7 Bel
Performance Seek	320 / 500 GB	2.8 Bel
	750 GB / 1 TB	2.9 Bel

*Notes:Design and specifications are subject to change without prior notice.

ENVIRONMENTAL SPECIFICATIONS

Temperature	
Operating	0~60°C
Non-operating	- 40~70°C
Humidity (non-condensing)	
Operating	5~90 %
Non-operating	5~95 %
Linear Shock (1/2 sine pulse)	
Operating	70 G
Non-operating	300 G
Altitude (relative to sea level)	
Operating	-300 to 3,000 m
Non-operating	-300 to 12,000 m

POWER REQUIREMENTS

Voltage	+5V±5%,+12V±10%	
Capacity[1]	320/500 GB	750 GB/1 TB
Spin Up Current (12V)	2.0 A	2.2 A
Seek[4]	5.7 W	6.9 W
Read/Write	6.1 W	7.4 W
Idle	5.0 W	6.4 W
Standby(typical)	1 W	1 W
Sleep(typical)	1 W	1 W

PHYSICAL DIMENSION

Height		26.1 mm
Width		101.5 mm
Length		147.0 mm
Weight (Max.)	320 / 500 GB	475 g
	750 GB / 1 TB	625 g

1 GB = 1 billion bytes, 1 TB = 1 trillion bytes.
Accessible capacity may vary as some OS uses binary numbering system for reported capacity
2. A small portion of the 8/16/32MB buffer memory is reserved for firmware use
3. Average value with a high performance cover.
4. Random seek with 30% duty cycle.(Average value)

Spinpoint F1DT

1 TB / 750 GB / 640 GB / 500 GB / 320 GB / 250 GB / 160 GB / 80 GB

Key Features

- Max. 334 GB Formatted Capacity per Disk
- Serial ATA 3.0 Gbps Interface Support
- Improved recording stability over temperature with PMR
- Advanced dynamic FOD control for best data integrity
- Intelligent compensation of external disturbance
- SATA Native Command Queuing Feature
- Device Initiated SATA Power Management
- Environment friendly product with RoHS compliance
- Rotational vibration sensor
- Improved performance with dual-ARM based firmware
- ATA S.M.A.R.T. Compliant
- ATA Automatic Acoustic Management Feature
- ATA 48-bit Address Feature
- ATA Device Configuration Overlay Feature
- NoiseGuard™
- SilentSeek™
- EcoSeek™

Application

Desktop PC / Digital TV / Home Media Servers

Specifications

Capacity[1]	80 GB	160 GB	250 GB	320 GB	500 GB	640 GB	750 GB	1 TB
8 MB	HD083GJ	HD161GJ	HD251HJ	HD321HJ	HD501IJ			
16 MB		HD162GJ	HD252HJ	HD322HJ	HD502IJ	HD642JI		
32 MB							HD753LJ	HD103UJ

DRIVE CONFIGURATIONS

Interface	Serial ATA 3.0 Gbps
Rotational Speed	7,200 RPM
Buffer DRAM Size[2]	8 / 16 / 32 MB
Sector Size	512 bytes

PERFORMANCE SPECIFICATIONS

Average Seek Time (typical)		8.9 ms
Average Latency		4.17 ms
Data Transfer Rate		
Media to/from Buffer (max.)		175 MB/sec
Buffer to/from Host (max.)		300 MB/sec
Drive Ready Time (typical)	80~320 GB	8 sec
	500 GB~1 TB	10~12 sec

RELIABILITY SPECIFICATIONS

Non-recoverable Read Error	1 sector in 10^{15} bits
Start/Stop Cycles	50,000

ACOUSTICS (AVERAGE SOUND POWER)[3]

Idle	80~320 GB	2.5 Bel
	500 GB-1 TB	2.7 Bel
Performance Seek	80~320 GB	2.8 Bel
	500 GB-1 TB	2.9 Bel

*Notes:Design and specifications are subject to change without prior notice.

ENVIRONMENTAL SPECIFICATIONS

Temperature	
Operating	0~60°C
Non-operating	- 40~70°C
Humidity (non-condensing)	
Operating	5~90 %
Non-operating	5~95 %
Linear Shock (1/2 sine pulse)	
Operating	70 G
Non-operating	300 G
Altitude (relative to sea level)	
Operating	-300 to 3,000 m
Non-operating	-300 to 12,000 m

POWER REQUIREMENTS

Voltage	+5V±5%,+12V±10%		
	80~320 GB	500/640 GB	750 GB/1 TB
Spin Up Current (12V)	2.0 A	2.3 A	2.4 A
Seek[4]	5.7 W	6.9 W	7.6 W
Read/Write	6.1 W	7.4 W	8.4 W
Idle	4.8 W	6.1 W	7.0 W
Standby(typical)	1 W	1 W	1 W
Sleep(typical)	1 W	1 W	1 W

PHYSICAL DIMENSION

Height		26.1 mm
Width		101.5 mm
Length		147.0 mm
Weight (Max.)	80~320 GB	470 g
	500/640 GB	610 g
	750 GB/1 TB	650 g

1. 1 GB = 1 billion bytes, 1 TB = 1 trillion bytes.
Accessible capacity may vary as some OS uses binary numbering system for reported capacity
2. A small portion of the 8/16/32MB buffer memory is reserved for firmware use
3. Average value with a high performance cover.
4. Random seek with 30% duty cycle.(Average value)

EcoGreen F3

1 TB / 750 GB / 500 GB / 320 GB / 250 GB

Key Features

- Max.500 GB Formatted Capacity Per Disk
- Serial ATA 3.0Gbps Interface Support
- Improved recording stability over temperature with PMR
- Advanced dynamic FOD control for best data integrity
- Intelligent compensation of external disturbance
- SATA Native Command Queuing Feature
- Device Initiated SATA Power Management
- Rotational vibration sensor(Optional)
- Environment friendly product with RoHS compliance
- Improved performance with dual-ARM based firmware
- ATA S.M.A.R.T. Compliant
- ATA Automatic Acoustic Management Feature
- ATA 48-bit Address Feature
- ATA Device Configuration Overlay Feature
- NoiseGuard™
- SilentSeek™
- EcoSeek™

Application

Desktop PC / Digital TV / Home Media Servers

Specifications

Capacity[1]	250 GB	320 GB	500 GB	750 GB	1 TB
16 MB 32 MB	HD253GI	HD324HI	HD503HI	HD754JI	HD105SI

DRIVE CONFIGURATION

Interface	Serial ATA 3.0 Gbps
Buffer DRAM Size[2]	16 / 32 MB
Sector Size	512 bytes

PERFORMANCE SPECIFICATIONS

Average Seek Time (typical)		8.9 ms
Average Latency		5.52 ms
Data Transfer Rate		
Media to/from Buffer (max.)		250 MB/sec
Buffer to/from Host (max.)		300 MB/sec
Drive Ready Time (typical)	250 ~ 500 GB	8 sec
	750 GB / 1 TB	10 sec

RELIABILITY SPECIFICATIONS

Non-recoverable Read Error	1 sector in 10^{15} bits
Start/Stop Cycles	50,000

ACOUSTICS [3]

Idle	250 ~ 500 GB	2.2 Bel
	750 GB / 1 TB	2.5 Bel
Performance Seek	250 ~ 500 GB	2.7 Bel
	750 GB / 1 TB	2.8 Bel

ENVIRONMENTAL SPECIFICATIONS

Temperature	
Operating	0~60°C
Non-operating	- 40~70°C
Humidity (non-condensing)	
Operating	5~90 %
Non-operating	5~95 %
Linear Shock (1/2 sine pulse)	
Operating	70 G
Non-operating	300 G
Altitude (relative to sea level)	
Operating	-300 to 3,000 m
Non-operating	-300 to 12,000 m

POWER REQUIREMENTS

Voltage	+5V±5%,+12V±10%	
Capacity[1]	250~500 GB	750 GB / 1 TB
Spin Up Current (12V)	2.0 A	2.2 A
Seek[4]	4.8 W	5.3 W
Read/Write	5.1 W	5.8 W
Idle (typical)	3.9 W	4.6 W
Standby(typical)	1 W	1 W
Sleep(typical)	1 W	1 W

PHYSICAL DIMENSION

Height		26.1 mm
Width		101.5 mm
Length		147.0 mm
Weight (Max.)	250 ~ 500 GB	475 g
	750 GB / 1 TB	625 g

* Notes : Design and specifications are subject to change without prior notice

1.1 GB = 1 billion bytes, 1 TB=1 trillion bytes.
* Accessible capacity may vary as some OS users binary numbering system for reported capacity
2. A small portion of the 16 / 32 MB buffer memory is reserved for firmware use
3. Average value with a high performance cover.
4. Random seek with 30% duty cycle.(Average value)

EcoGreen F3EG

2 TB / 1.5 TB

Key Features

- Max.500 GB Formatted Capacity Per Disk
- Environment friendly product with RoHS compliance
- Serial ATA 3.0 Gbps Interface Support
- Improved performance with dual-ARM based firmware
- Improved recording stability over temperature with PMR
- ATA S.M.A.R.T. Compliant
- Advanced dynamic FOD control for best data integrity
- ATA Automatic Acoustic Management Feature
- Intelligent compensation of external disturbance
- ATA 48-bit Address Feature
- SATA Native Command Queuing Feature
- ATA Device Configuration Overlay Feature
- Device Initiated SATA Power Management
- NoiseGuard™
- Rotational vibration sensor
- SilentSeek™
- EcoSeek™

Application

Desktop PC / Digital TV / Home Media Servers

Specifications

Capacity[1]	1.5 TB	2 TB
32 MB	HD153WI	HD203WI

DRIVE CONFIGURATION

Interface	Serial ATA 3.0 Gbps
Buffer DRAM Size[2]	32 MB
Sector Size	512 bytes

PERFORMANCE SPECIFICATIONS

Average Seek Time (typical)	8.9 ms
Average Latency	5.56 ms
Data Transfer Rate	
Media to/from Buffer (max.)	153 MB/sec
Buffer to/from Host (max.)	300 MB/sec
Drive Ready Time (typical)	15 sec

RELIABILITY SPECIFICATIONS

Non-recoverable Read Error	1 sector in 10^{15} bits
Load/Unload Cycles (ambient)	300,000

ACOUSTICS [3]

Idle (typ/max)	2.6/2.7 Bel
Performance Seek (typ/max)	2.9/3.1 Bel
Quiet seek (typ/max)	2.8/2.9 Bel

ENVIRONMENTAL SPECIFICATIONS

Temperature	
Operating	0~60°C
Non-operating	- 40~70°C
Humidity (non-condensing)	
Operating	5~90 %
Non-operating	5~95 %
Linear Shock (1/2 sine pulse)	
Operating	70 G
Non-operating	250 G
Altitude (relative to sea level)	
Operating	-300 to 3,000 m
Non-operating	-300 to 12,000 m

POWER REQUIREMENTS

Voltage	+5V±5%, +12V±10%
Capacity[1]	2 TB
Spin-up Current (Max.)	2.0 A
Random Seek[3]	7.2 W
Read/Write On Track	6.3 W
Idle (typical)	5.5 W
Standby (typical)	1 W
Sleep (typical)	1 W

PHYSICAL DIMENSION

Height	26.1 mm
Width	101.5 mm
Length	147.0 mm
Weight (avg.)	690 g

*Notes:Design and specifications are subject to change without prior notice.

1.1 MB = 1,000,000 Bytes, 1 GB=1,000,000,000 Bytes.
2. A small portion of the 32MB buffer memory is reserved for firmware use.
3 Random seek with 30% duty cycle.(Average value).

EcoGreen F2

1.5 TB / 1 TB / 500 GB

Key Features

- Max.500 GB Formatted Capacity Per Disk
- Environment friendly product with RoHS compliance
- Serial ATA 3.0 Gbps Interface Support
- Improved performance with dual-ARM based firmware
- Improved recording stability over temperature with PMR
- ATA S.M.A.R.T. Compliant
- Advanced dynamic FOD control for best data integrity
- ATA Automatic Acoustic Management Feature
- Intelligent compensation of external disturbance
- ATA 48-bit Address Feature
- SATA Native Command Queuing Feature
- ATA Device Configuration Overlay Feature
- Device Initiated SATA Power Management
- NoiseGuard™
- Rotational vibration sensor
- SilentSeek™
- EcoSeek™

Application

Desktop PC / Digital TV / Home Media Servers

Specifications

Capacity[1]	500 GB	1 TB	1.5 TB
16 MB	HD502HI	HD102SI	HD153UI
32 MB		HD103SI	HD154UI

DRIVE CONFIGURATION

Interface	Serial ATA 3.0 Gbps
Buffer DRAM Size[2]	16 / 32 MB
Sector Size	512 bytes

PERFORMANCE SPECIFICATIONS

Average Seek Time (typical)		8.9 ms
Average Latency		5.6 ms
Data Transfer Rate		
Media to/from Buffer (max.)		166 MB/sec
Buffer to/from Host (max.)		300 MB/sec
Drive Ready Time (typical)	500 GB	8 sec
	1 TB	11 sec
	1.5 TB	13 sec

RELIABILITY SPECIFICATIONS

Non-recoverable Read Error	1 sector in 10^{15} bits
Start/Stop Cycles	50,000

ACOUSTICS [3]

Idle	500 GB	2.2 Bel
	1/1.5 TB	2.5 Bel
Performance Seek	500 GB	2.7 Bel
	1/1.5 TB	2.8 Bel

*Notes:Design and specifications are subject to change without prior notice.

ENVIRONMENTAL SPECIFICATIONS

Temperature	
Operating	0~60°C
Non-operating	- 40~70°C
Humidity (non-condensing)	
Operating	5~90 %
Non-operating	5~95 %
Linear Shock (1/2 sine pulse)	
Operating	70 G
Non-operating	300 G
Altitude (relative to sea level)	
Operating	-300 to 3,000 m
Non-operating	-300 to 12,000 m

POWER REQUIREMENTS

Voltage		+5V±5%,+12V±10%	
Capacity[1]	500 GB	1 TB	1.5 TB
Spin Up Current (Max)	2.0 A	2.0 A	2.0 A
Seek[4]	4.8 W	5.3 W	5.7 W
Read/Write	5.1 W	5.8 W	6.3 W
Idle (typical)	3.9 W	4.6 W	5.1 W
Standby (typical)	1 W	1 W	1 W
Sleep (typical)	1 W	1 W	1 W

PHYSICAL DIMENSION

Height		26.1 mm
Width		101.5 mm
Length		147.0 mm
Weight (Max.)	500 GB	470 g
	1 TB	610 g
	1.5 TB	650 g

1. 1 GB = 1 billion bytes, 1 TB = 1 trillion bytes. Accessible capacity may vary as some OS uses binary numbering system for reported capacity
2. A small portion of the 8/16/32MB buffer memory is reserved for firmware use
3. Average value with a high performance cover.
4. Random seek with 30% duty cycle.(Average value)

EcoGreen F1DT

1 TB / 750 GB / 640 GB / 500 GB / 320 GB / 250 GB

Key Features

- Max. 334 GB Formatted Capacity per Disk
- Serial ATA 3.0 Gbps Interface Support
- Improved recording stability over temperature with PMR
- Advanced dynamic FOD control for best data integrity
- Intelligent compensation of external disturbance
- SATA Native Command Queuing Feature
- Device Initiated SATA Power Management
- Environment friendly product with RoHS compliance
- Improved performance with dual-ARM based firmware
- ATA S.M.A.R.T. Compliant
- ATA Automatic Acoustic Management Feature
- ATA 48-bit Address Feature
- ATA Device Configuration Overlay Feature
- NoiseGuard™
- SilentSeek™
- EcoSeek™

Application

Desktop PC / Digital TV / Home Media Servers

Specifications

Capacity[1]	250 GB	320 GB	500 GB	640 GB	750 GB	1 TB
16 MB	HD252HI	HD322HI	HD502JI	HD642JI		
32 MB					HD753LI	HD103UI

DRIVE CONFIGURATIONS

Interface	Serial ATA 3.0 Gbps
Buffer DRAM Size[2]	16 / 32 MB
Sector Size	512 bytes

PERFORMANCE SPECIFICATIONS

Seek Time (typical)		
Average		8.9 ms
Average Latency		5.56 ms
Data Transfer Rate		
Media to/from Buffer (max.)		140 MB/sec
Buffer to/from Host (max.)		300 MB/sec
Drive Ready Time (typical)	250-320 GB	8 sec
	500 GB~1 TB	12 sec

RELIABILITY SPECIFICATIONS

Non-recoverable Read Error	1 sector in 10^{15} bits
Start/Stop Cycles	50,000

ACOUSTICS (AVERAGE SOUND POWER)[3]

Idle	250-320 GB	2.2 Bel
	500 GB-1 TB	2.5 Bel
Performance Seek	250-320 GB	2.7 Bel
	500 GB-1 TB	2.8 Bel

*Notes:Design and specifications are subject to change without prior notice.

ENVIRONMENTAL SPECIFICATIONS

Temperature	
Operating	0~60°C
Non-operating	- 40~70°C
Humidity (non-condensing)	
Operating	5~90 %
Non-operating	5~95 %
Linear Shock (1/2 sine pulse)	
Operating	70 G
Non-operating	300 G
Altitude (relative to sea level)	
Operating	-300 to 3,000 m
Non-operating	-300 to 12,000 m

POWER REQUIREMENTS

Voltage		+5V±5%,+12V±10%	
	250/320 GB	500/640 GB	750 GB/1 TB
Spin Up Current (12V)	2.0 A	2.0 A	2.0 A
Seek[4]	4.8 W	5.2 W	5.7 W
Read/Write	5.1 W	5.6 W	6.3 W
Idle	3.9 W	4.4 W	5.1 W
Standby(typical)	1 W	1 W	1 W
Sleep(typical)	1 W	1 W	1 W

PHYSICAL DIMENSION

Height		26.1 mm
Width		101.5 mm
Length		147.0 mm
Weight (Max.)	250/320 GB	470 g
	500/640 GB	610 g
	750 GB/1 TB	650 g

1. 1 GB = 1 billion bytes, 1 TB = 1 trillion bytes. Accessible capacity may vary as some OS uses binary numbering system for reported capacity
2. A small portion of the 8/16/32MB buffer memory is reserved for firmware use
3. Average value with a high performance cover.
4. Random seek with 30% duty cycle.(Average value)



Mobile HDD

Spinpoint M7 (Enhanced)
Spinpoint M7U / Spinpoint M7

True mobility in your imagination can be realized with desktop-compatible capacity, quietest operation, and longer battery life.

Spinpoint M7 (Enhanced)

640GB / 500GB / 320GB / 250GB / 160GB

Key Features

- Max. 320 GB formatted capacity per disk
- Serial ATA 3.0Gbps Interface Support
- SATA Native Command Queuing Feature
- TuMR/PMR head with FOD technology
- Load/Unload Head Technology
- ATA Security Mode Feature Set
- ATA S.M.A.R.T. Feature Set
- SilentSeek™
- NoiseGuard™
- EcoSeek™

Application

Slim PC / Note PC / Car Entertainment System / blade Server

Specifications

Capacity[1]	160 GB	250 GB	320 GB	500 GB	640 GB
8 MB	HM161GI	HM251HI	HM321HI	HM501II	HM641JI

DRIVE CONFIGURATION

Interface	SATA 3.0 Gbps
Rotational Speed	5,400 RPM
Buffer DRAM Size[2]	8 MB
Sector Size	512 bytes

PERFORMANCE SPECIFICATIONS

Average Seek Time (typical)	12 ms
Data Transfer Rate	
Media to/from Buffer (max.)	138 MB/sec
Buffer to/from Host (max.)	300 MB/sec
Drive Ready Time (typical)[3]	4 sec

RELIABILITY SPECIFICATIONS[3]

Non-recoverable Read Error	1 sector in 10^{14} bits
Controlled Ramp Load/Unload	600,000

ACOUSTICS (AVERAGE SOUND POWER)

Idle(typical)	2.4 Bel
Performance Seek[4]	2.6 Bel

*Notes:Design and specifications are subject to change without prior notice.

ENVIRONMENTAL SPECIFICATIONS

Temperature	
Operating	5~55°C
Non-operating	- 40~70°C
Humidity (non-condensing)	
Operating	5~90 %
Non-operating	5~95 %
Linear Shock (1/2 sine pulse)	
Operating	400 G
Non-operating	900 G
Vibration	
Operating (Random, 10~500Hz)	1.5 Grms
Altitude (relative to sea level)	
Operating	-300 to 3,000 m
Non-operating	-400 to 15,000 m

POWER REQUIREMENTS

Voltage	+5V±5%
Spin Up Current (Max.)	1000 mA
Seek (avg)[3]	2.5 W
Read/Write (avg)	2.5 W
Low Power Idle (avg)	0.85 W
Standby (avg)	0.25 W
Sleep (avg)	0.2 W

PHYSICAL DIMENSION

Height (max.)	9.5 mm
Width	69.85 mm
Length (max.)	100 mm
Weight (max.)	105 g

1.1 MB = 1,000,000 Bytes, 1 GB = 1,000,000,000 Bytes
Accessible capacity may vary as some OS uses binary numbering system for reported capacity
2. A small portion of the 8MB buffer memory is reserved for firmware use
3. Power-On to Drive Ready
4. 30% duty cycle, random seek

Spinpoint M7U

500 GB / 320 GB / 250 GB / 160 GB

Key Features

- Max. 250 GB formatted capacity per disk
- TuMR/PMR head with FOD technology
- USB 2.0 Interface Support
- Load/Unload Head Technology
- SilentSeek™
- NoiseGuard™
- EcoSeek™

Application

External Storage

Specifications

Capacity[1]	160 GB	250 GB	320 GB	500 GB
8 MB	HM162HX	HM252HX	HM322IX	HM502JX

DRIVE CONFIGURATION

Interface	USB 2.0
Rotational Speed	5,400 RPM
Buffer DRAM Size[2]	8 MB
Sector Size	512 bytes

PERFORMANCE SPECIFICATIONS

Average Seek Time (typical)	12 ms
Data Transfer Rate	
Media to/from Buffer (max.)	138 MB/sec
Buffer to/from Host (max.)	60 MB/sec
Drive Ready Time (typical)[3]	4sec

RELIABILITY SPECIFICATIONS

Non-recoverable Read Error	1 sector in 10^{14} bits
Controlled Ramp Load/Unload	600,000

ACOUSTICS (AVERAGE SOUND POWER)[3]

Idle (typical)	2.4 Bel
Performance Seek (typical)	2.6 Bel

*Notes:Design and specifications are subject to change without prior notice.

ENVIRONMENTAL SPECIFICATIONS

Temperature	
Operating	5~55°C
Non-operating	- 40~70°C
Humidity (non-condensing)	
Operating	5~90 %
Non-operating	5~95 %
Linear Shock (1/2 sine pulse)	
Operating	300 G
Non-operating	900 G
Vibration	
Operating (Random, 10~500Hz)	0.9 Grms
Altitude (relative to sea level)	
Operating	-300 to 3,000 m
Non-operating	-400 to 15,000 m

POWER REQUIREMENTS

Voltage	+5V±5%
Spin Up Current (Max.)	750 mA
Seek (typical)	2.8 W
Read/Write (typical)	3.2 W
Idle (typical)	1.6 W
Standby (typical)	1.2 W
Sleep (typical)	1.2 W

PHYSICAL DIMENSION

Height	9.5 mm
Width	69.85 mm
Length	104 mm
Weight (max.)	105 g

1.1MB = 1,000,000 Bytes, 1GB = 1,000,000,000 Bytes
Accessible capacity may vary as some OS uses binary numbering system Read/Write (avg.) 3.2 W for reported capacity
2. A small portion of the 8MB buffer memory is reserved for firmware use Standby (avg.) 1.2 W
3. Power-On to Drive Ready Sleep (avg.l) 1.2 W
4. 30% duty cycle, random seek
5. On Track Read Operation

Spinpoint M7

500 GB / 400 GB / 320 GB / 250 GB

Key Features

- Max. 250 GB formatted capacity per disk
- SATA Native Command Queuing Feature
- TuMR/PMR head with FOD technology
- Serial ATA 3.0 Gbps Interface Support
- Load/Unload Head Technology
- ATA Security Mode Feature Set
- ATA S.M.A.R.T. Feature Set
- SilentSeek™
- NoiseGuard™
- EcoSeek™

Application

Slim PC / Note PC / Car Entertainment System / blade Server

Specifications

Capacity[1]	250 GB	320 GB	400 GB	500 GB
8 MB	HM250HI	HM320II	HM400JI	HM500JI

DRIVE CONFIGURATION

Interface	SATA 3.0 Gbps
Rotational Speed	5,400 RPM
Buffer DRAM Size[2]	8 MB
Sector Size	512 bytes

PERFORMANCE SPECIFICATIONS

Average Seek Time (typical)	12 ms
Data Transfer Rate	
Media to/from Buffer (max.)	138 MB/sec
Buffer to/from Host (max.)	300 MB/sec
Drive Ready Time (typical)[3]	4 sec

RELIABILITY SPECIFICATIONS

Non-recoverable Read Error	1 sector in 10^{14} bits
Controlled Ramp Load/Unload	600,000

ACOUSTICS (AVERAGE SOUND POWER)[5]

Idle (typical)	2.4 Bel
Performance Seek (typical)	2.6 Bel

*Notes:Design and specifications are subject to change without prior notice.

ENVIRONMENTAL SPECIFICATIONS

Temperature	
Operating	5~55°C
Non-operating	- 40~70°C
Humidity (non-condensing)	
Operating	8~90 %
Non-operating	5~95 %
Linear Shock (1/2 sine pulse)	
Operating	400 G
Non-operating	900 G
Vibration	
Operating (Random, 10~500Hz)	1.5 Grms
Altitude (relative to sea level)	
Operating	-300 to 3,000 m
Non-operating	-400 to 15,000 m

POWER REQUIREMENTS

Voltage	+5V±5%
Spin Up Current (Max.)	1000 mA
Seek (avg)[4]	2.5 W
Read/Write (avg)	2.5 W
Low Power Idle (avg)	0.85 W
Standby (avg)	0.25 W
Sleep (avg.I)	0.2 W

PHYSICAL DIMENSION

Height	9.5 mm
Width	69.85 mm
Length	100.0 mm
Weight (max.)	105 g

* Note : Design and specifications are subject to change without prior notice.
1. 1 MB = 1,000,000 Bytes, 1 GB = 1,000,000,000 Bytes, Accessible capacity may vary as some OS uses binary numbering system for reported capacity
2. A small portion of the 8MB buffer memory is reserved for firmware use
3. Power-On to Drive Ready
4. 30% duty cycle, random seek
5. On Track Read Operation

Samsung Electronics

We provide the most reliable storage solution

Line-up

SAMSUNG HARD DISK DRIVE 2009 PRODUCT LIST

F/Factor	Family	Model	Capacity(GB)	RPM	Interface	Buffer	Sector size
Desktop HDD	F3	HD164GJ	160	7200	SATA 3.0 Gbps	8	512
		HD254GJ	250	7200	SATA 3.0 Gbps	8	512
		HD324HJ	320	7200	SATA 3.0 Gbps	8	512
		HD163GJ	160	7200	SATA 3.0 Gbps	16	512
		HD253GJ	250	7200	SATA 3.0 Gbps	16	512
		HD323HJ	320	7200	SATA 3.0 Gbps	16	512
		HD502HJ	500	7200	SATA 3.0 Gbps	16	512
		HD754JJ	750	7200	SATA 3.0 Gbps	32	512
		HD103SJ	1TB	7200	SATA 3.0 Gbps	32	512
	F1DT	HD083GJ	80	7200	SATA 3.0 Gbps	8	512
		HD161GJ	160	7200	SATA 3.0 Gbps	8	512
		HD251HJ	250	7200	SATA 3.0 Gbps	8	512
		HD321HJ	320	7200	SATA 3.0 Gbps	8	512
		HD501IJ	500	7200	SATA 3.0 Gbps	8	512
		HD162GJ	160	7200	SATA 3.0 Gbps	16	512
		HD252HJ	250	7200	SATA 3.0 Gbps	16	512
		HD322HJ	320	7200	SATA 3.0 Gbps	16	512
		HD502IJ	500	7200	SATA 3.0 Gbps	16	512
		HD642JJ	640	7200	SATA 3.0 Gbps	16	512
		HD753LJ	750	7200	SATA 3.0 Gbps	32	512
		HD103UJ	1 TB	7200	SATA 3.0 Gbps	32	512
	F3EG	HD253GI	250		SATA 3.0 Gbps	16	512
		HD324HI	320		SATA 3.0 Gbps	16	512
		HD503HI	500		SATA 3.0 Gbps	16	512
		HD754JI	750		SATA 3.0 Gbps	32	512
		HD105SI	1TB		SATA 3.0 Gbps	32	512
	F2EG	HD502HI	500		SATA 3.0 Gbps	16/32	512
		HD102SI	1 TB		SATA 3.0 Gbps	16/32	512
		HD103SI	1 TB		SATA 3.0 Gbps	16/32	512

F/Factor	Family	Model	Capacity(GB)	RPM	Interface	Buffer	Sector size
Desktop HDD	F2EG	HD153UI	1.5 TB		SATA 3.0 Gbps	16/32	512
		HD154UI	1.5 TB		SATA 3.0 Gbps	16/32	512
	F1EG	HD252HI	250		SATA 3.0 Gbps	16	512
		HD322HI	320		SATA 3.0 Gbps	16	512
		HD502JI	500		SATA 3.0 Gbps	16	512
		HD642JI	640		SATA 3.0 Gbps	16	512
		HD753LI	750		SATA 3.0 Gbps	32	512
		HD103UI	1 TB		SATA 3.0 Gbps	32	512
Mobile HDD	M7 (Enhanced)	HM161GI	160	5400	SATA 3.0Gbps	8	512
		HM251HI	250	5400	SATA 3.0Gbps	8	512
		HM321HI	320	5400	SATA 3.0Gbps	8	512
		HM501JI	500	5400	SATA 3.0Gbps	8	512
		HM641JI	640	5400	SATA 3.0Gbps	8	512
	M7U	HM162HX	160	5400	USB 2.0	8	512
		HM252HX	250	5400	USB 2.0	8	512
		HM322IX	320	5400	USB 2.0	8	512
		HM502JX	500	5400	USB 2.0	8	512
	M7	HM250II	250	5400	SATA 3.0 Gbps	8	512
		HM320HI	320	5400	SATA 3.0 Gbps	8	512
		HM400HI	400	5400	SATA 3.0 Gbps	8	512
		HM500JI	500	5400	SATA 3.0 Gbps	8	512

Why Samsung Hard Disk Drive?

Our quality is based on our ACCESS TO FUNDAMENTAL TECHNOLOGY, not only for Samsung's own R&D resources within the HDD division, but also from various R&D resources within the Samsung group. SAIT(Samsung Advanced Institute of Technology) developed Acoustic Noise Suppression Technology, which is utilized in all Samsung HDDs. SAIT also provides Head Stack, Read Channel, Spindle Motor, Servo Control System and Optical Technologies. Similarly, Samsung Electronic's corporate R&D center developed vibration suppression technology.

MEMO

MEMO

WORLDWIDE MAGAZINE AWARDS